

# Ultrasonic Level Transmitter



## General Description

Efficiently monitor fluid levels with our ultrasonic level transmitter, a robust solution designed for precise measurement in various industrial applications. Featuring advanced ultrasonic technology, this transmitter offers reliable performance, delivering accurate data even in challenging environments. It ensures easy installation and seamless integration into existing systems. Built to withstand harsh conditions, it provides long-term durability and minimal maintenance requirements, guaranteeing uninterrupted operation

## Features

- 2 or 4 wire compact transmitters.
- Non-contact level metering.
- Narrow 5° beam angle.
- PP, PVDF, PTFE, stainless steel or foam faced transducers.
- Plastic or Aluminium housing.
- Optional Display
- Optional Bluetooth connectivity

## Technical Specifications

Range	0 - 10 m, 0-20 m, 0-30 m
Accuracy	+/- 0.5% FS
Material	PVC/ SS
Power supply	18 - 32 V DC
Operating temperature	-20°C to 70°C
Output	4 - 20 mA/ RS485 (Modbus RTU)
Degree of protection	IP-67

Note: Due to continuous improvement, specifications are subject to change without prior notice.



Plot No. 30, Gat No. 396, Near IT Park,  
Dehu-Alandi Road, Talawade, Pune -  
411062, Maharashtra, India  
Phone: + 91 98224 21087 / + 91 98810 63875  
Email: [response@crystalvision9.com](mailto:response@crystalvision9.com)  
Web: [www.crystalvision9.com](http://www.crystalvision9.com)